


Drying Cabinet ProLine FC 20



Drying Cabinet for Heavy Duty Garments

ProLine FC 20 is a drying cabinet with a capacity of 20 kg. It dries heavy duty garments both efficient and gentle. The drying programs reduce wear and tear, and are developed to dry heavy work suits.



Double air flow = short
drying time

FC 20 is equipped with specially designed hangers, to dry the textiles from both the inside and the outside. This system dries heavy clothing very fast. The drying process has no mechanical action which extends the life span of the garments. FC 20 has optional hangers to dry boots and gloves etc.

One program for timed drying and three automatic programs, with the Humidity Tracking System (HTS). HTS is a system that measures the level of humidity every second, to determine exactly when the textiles are dry. Programs can be adjusted for other garments. All automatic programs can be set for drying temperature, reactivation of impregnation (overheat mode) and cool down.

Standard

- Drying capacity of 6 large fire suits equal to 20 kg
- Drying process from the outside and inside
- Adjustable programs
- Drying procedure hardens the impregnation
- Gentle drying without friction
- Three automatic programs and one program for timed drying
- Indoor lighting
- Program ends with "cool down" to room temperature
- Standard recirculation system, hot air
- Delivered as flat-pack to save shipping costs

Options:



Racks

Racks for gloves and boots. Hot air is directed into each glove (max 4 pairs) or boot (max 2 pairs).

For gloves, part no 131008
For boots, part no 131009



Goud
Laundry
Solutions
Drying cabinet
FC20

HTS...
Humidity Tracking System



Ideal for delicate garments
that are not suitable to
tumble dry.

Main specifications

	FC 20
Loading capacity, kg/lbs	20/44
Loading capacity, complete fire suits	6
Drying time, min*	175
Heating effect, kW	12
Evacuated air, max, m ³ /h	600
Total effect, kW	12,45
Energy consumption/kg, kWh	0,98
Part no	131035

*Drying of 6 heavy duty garments with membrane (dry weight 20 kg), washed and high-spinned to 50% residual moisture, dried to 4% residual moisture.

Our manufacturer uses: Certways templates and guidelines for environmental and quality management in accordance with ISO 14001:2004 and ISO 9001:2008.

GOUD
Laundry Solutions

info@laundrysolutions.nl

www.laundrysolutions.nl

tel: +31-186576050

fax: +31-186575047



GOUD LAUNDRY SOLUTIONS – PAUKENSLAG 1 – 3286TD – KLAASWAAL

TEL: 0186-576050 – FAX: 0186-575047 - INFO@LAUNDRIESOLUTIONS.NL - WWW.LAUNDRIESOLUTIONS.NL

FC 20

Electrical connections	
Electrical connection*	3~N, 400 V, 50 Hz
Fuse, A	20
Total effect, kW	12,45
Heating elements, kW	12

Air connections	
Outlet exhaust, \varnothing mm/inch	160/6,3
Outlet air flow, m ³ /h**	300
Pressure drop, max Pa**	210

Sound level	
Airborne sound level, dB(A)	65

Shipping data	
Net, kg/lbs	200/441
Crated, kg/lbs	40/88,2
Shipping data net, kg/lbs	240/529
Shipping volume, m ³	1,76

Optional extras	
Air exchanger 2 vent., 160mm/3,6 inch	141018
Rack for gloves	131008
Rack for boots	131009
Frame of hooks, set of 3	131071

Dimensions	
Width, mm/inch	1800/71
Depth, mm/inch	800/31,5
Height, inner, mm/inch	1752/69
Height, outer, mm/inch	1955/77

* Other voltage on request

** Recommended air flow

